



# **PERFORMA SYNTHETIC SAE 5W-40**

## **(For Export Only)**

### Premium Performance Fully Synthetic Gasoline Engine Oil

#### Product Description

- **PERFORMA SYNTHETIC:** Premium performance, fully synthetic multigrade SAE 5W-40 "Next Generation" gasoline engine oils exceeding the highest quality standard of API (API SN), European Standard and OEM Specifications. Specifically formulated from selected synthetic base fluids and hi-tech additive compatible with the future low emission engines (EURO IV)

#### Features/Benefits

- Provides high thermal stability and oxidation resistance, excellent protection against filter blocking and sludge formation
- Enhances deposit control and consistent cleanliness of engines parts
- Offers better lubrication and additional wear protection at start-up and under all operating conditions
- Improves fuel economy and low oil consumption
- Excellent seal compatibility
- Extends oil drain interval and the service period of catalytic converter

#### Applications

- Recommended for use in all types of high performance gasoline vehicles and imported cars as well as the ones with carburetors and electronic injectors where better lubricity capability and longer engine life are provided. It is also suitable for use in diesel pickups and passenger cars which requiring API CF.

#### Reference Standards

- |              |                                  |
|--------------|----------------------------------|
| - API SN/CF  | - ACEA A3/B3-08, A3/B4-08, C3-08 |
| - MB p229.31 | - VW 502.00/505.00               |
| - BMW LL-04  | - Porsche A40                    |

#### Key Properties

	SAE 5W-40
- Viscosity @ 100 °C, cSt	14.3
- Viscosity Index	173
- Cold-cranking Simulator, @ -30 °C, cP	5,410
- Flash Point , (COC) , °C	240
- Pour Point , °C	-45

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985  
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878