

**PERFORMA SYNTHETIC NGV****Premium Performance Engine Oil for Bi-fuel Vehicles**

## Product Description

- **PERFORMA SYNTHETIC NGV:** Premium performance, fully synthetic, step change of multigrade SAE 5W-40 engine oil exceeding the highest quality standard of API (API SN). Specially formulated from premium quality synthetic basestocks with the unique combination of exceptional additive technology to deliver the ultimate performance of oxidation and nitration resistance and the superior performance in sludge and wear protection for high performance passenger car with bi-fuel engines (capable of the alternate use in natural gas and gasoline/gasohol).

## Features/Benefits

- Delivers excellent lubrication and engine protection even in high temperature operating conditions of gaseous fueled engines
- Resists to oxidation and nitration exceptionally, and provides greater thermal stability
- Prevents engine against wear and corrosion under all operating conditions
- Provides superior sludge protection and enhances deposit control
- Field proven with bi-fuel passenger cars under the most extreme driving conditions

## Applications

- Recommended for use in high performance bi-fuel vehicles or after-market (retrofit) bi-fuel vehicles (either in Gasoline - CNG or Gasoline - LPG). Also suitable for high performance passenger car with gasoline engines requiring API SN or lower performance lubricants such as API SM, SL, SJ.

## Reference Standards

- API SN/CF
- ACEA A3-02

## Key Properties

	SAE 5W-40
- Viscosity @ 100 °C, cSt	14.5
- Viscosity Index	170
- Cold-cranking Simulator, @ -25 °C, cP	5,885
- Flash Point , (COC) , °C	232
- Pour Point , °C	-42

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985  
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878