



# PERFORMA GAS TECH

## High Performance Engine Oil for Bi-fuel Vehicles

### Product Description

- **PERFORMA GASTECH** : High performance, semi-synthetic multigrade SAE 15W-40 engine oil with the highest quality standard of API (API SN). Specially formulated from high quality base oil, strengthened with synthetic base stock and high performance additives specifically selected to provide better performances and durability. Suitable for commercial passenger cars running with CNG (NGV)/ LPG and gasoline fuel such as taxi and van.

### Features/Benefits

- Provides superior thermal stability, oxidation stability and nitration resistance
- Provides better lubrication and engine wear protection under all operating conditions
- Keeps engines cleaner and protects against deposits and sludge formation
- Reduce engine oil top-up rate for long run driving

### Applications

- Recommended for use in OEMs bi-fueled vehicles or after-market (retrofit) bi-fueled vehicles (either in Gasoline - CNG or Gasoline - LPG). Especially suitable for taxi and van gasoline engines requiring API SN or lower performance lubricants such as API SM, SL and SJ.

### Reference Standards

- API SN

### Key Properties

|                                         | SAE 15W-40 |
|-----------------------------------------|------------|
| - Viscosity @ 100 °C, cSt               | 15.45      |
| - Viscosity @ 40 °C, cSt                | 119.0      |
| - Viscosity Index                       | 136        |
| - Total Base Number, mgKOH/g            | 9.24       |
| - Density @ 15 °C, g/cm <sup>3</sup>    | 0.8691     |
| - Cold-cranking Simulator, @ -20 °C, cP | 6,418      |
| - Flash Point , (COC) , °C              | 246        |
| - Pour Point , °C                       | -36        |

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 8182, 8278  
Fax. (662) 537- 3000 Ext. 8146 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412-13.