



DYNAMIC PREMIER

High Performance Semi-Synthetic Diesel Engine Oil for Pickup Trucks

Product Description

- **DYNAMIC PREMIER** : A high performance, semi-synthetic, multigrade SAE 15W-40 diesel engine oil exceeding the requirements of API CI-4, specially designed for modern diesel engine especially high speed pickup trucks. Formulated with a balanced blend of synthetic base oil and exceptionally selected additives to increase soot handling ability, detergency and lubricity efficiency

Features/Benefits

- Enhances soot control and prevents the build-up of deposits, sludge and varnish with DDL Booster Technology
- Offers enhanced engine performance and increases engine wear and corrosion protection
- Provides high film strength, better lubrication and thermal & oxidation stability in all service conditions
- Improves fuel economy and minimizes engine oil consumption
- Prolongs engine life and enables longer oil drain intervals

Applications

- Recommended for high performance diesel engines, especially new models of pickup truck, MPV, SUV and Off-road driving vehicles
- Naturally aspirated or turbocharged, hi-speed, 4 wheel drive and heavy duty vehicles in all service conditions
- Commercial road transport in light, medium and heavy-duty service

Performance Standards

- | | | |
|-----------------------------------|----------------------|------------------|
| - API CI-4, CH-4, CG-4, CF-4 / SL | - ACEA E7-08 | - JASO DH-1 |
| - MACK EO-M Plus | - MB 228.3 | - MAN M3275-1 |
| - CUMMINS CES 20078/ 20077/ 20076 | - MTU Type 2 | - VOLVO VDS-3 |
| - RENAULT VI RLD-2 | - CATERPILLAR ECF-1a | - DETROIT 93K215 |

Key Properties

	SAE 15W-40		SAE 15W-40
- Viscosity @ 100 °C, cSt	14.9	- Pour Point , °C	-36
- Viscosity @ 40 °C, cSt	107.6	- Flash Point (COC), °C	244
- Viscosity Index	144	- Density @ 15 °C, g/cm ³	0.866
- Cold-cranking Simulator @ -20°C, cP	5,278	- Sulfate Ash (%wt.)	1.42
- Total Base Number, mgKOH/g	10.2		

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878