

## High Performance Single grade Diesel Engine Oil

### Product Descriptions

- **DYNAMIC XJ** : High Performance, single grade, heavy duty diesel engine oil with API CF quality standard upgraded in all aspect, especially for enabling the engine oil to disperse soot caused by incomplete combustion

### Features/Benefits

- Increases engine wear and corrosion protection
- Provides super deposit cleanliness and soot dispersant
- Completely prevents engine oil from sludge formation
- High base number enabling to neutralize acids caused by combustion

### Applications

- Recommended for all types of heavy duty vehicles or engines
- Recommended for engines with turbocharger or turbo inter-cooler
- Highly recommended for indirect injection (IDI) engines or using low quality fuel

### Reference Standards

- |             |               |
|-------------|---------------|
| - API CF/SF | - ACEA E2     |
| - MB 228.0  | - JASO DH-1   |
| - MAN 270   | - ALLISON C-4 |

### Key Properties

	SAE 40		SAE 40
- Viscosity @ 100 °C, cSt	14.9	- Density @ 15 °C, g/cm <sup>3</sup>	0.898
- Viscosity @ 40 °C, cSt	146	- Flash Point (COC), °C	260
- Viscosity Index	102	- Pour Point, °C	-24
- Total Base Number, mgKOH/g	12.0	- Sulfated Ash, %wt	1.64

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985  
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878