

## 2T Motorcycle Engine Oil

### Product Description

- *HI-SPEED 2T* : Two-stroke motorcycle engine oil that exceeds high performance level of JASO FC standard and TIS 1040-1998.

### Features/Benefits

- Formulates with PIB (Polyisobutylene) synthetic base stock for extremely clean combustion and reduces white smoke and deposits
- Increases lubricity efficiency and provides good engine cleanliness
- Prevents piston and ring sticking and spark plug fouling
- Protects exhaust port blocking

### Applications

- Recommended for all air-cooled 2-stroke motorcycle engines, lawn mowers, chain saws and portable generator

### Reference Standards

Exceeds high performance level of :

- JASO FC (JASO Identification No. 066PTT006)
- API TC
- TIS 1040-1998

### Key Properties

- |                             |      |
|-----------------------------|------|
| - Viscosity @ 100 °C, cSt   | 11.3 |
| - Viscosity Index           | 118  |
| - Flash Point , (PMCC) , °C | 92   |
| - Sulfated Ash, %wt         | 0.08 |

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241  
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.