

Automotive Gear Oil

Product Description

- PTT G-100: A multipurpose manual transmission oil which is produced from high quality base oils and selected additives, is suitable for automotive gear that requires GL-4 standard

Features/Benefits

- Provide high resistant on water and oxygen combination
- Resist to wear formation and protect against corrosion on copper parts
- Protect harmful sludge and rust formation

Applications

- Recommended for use in manual transmissions, synchromesh gears, rear axles and the other axles in moderate operating conditions

Performance Standards

- API GL-4
- MIL-L-2105

			Key Properties
	SAE 80W-90	SAE 90	SAE 140
- Viscosity @ 100 °C, cSt	14.9	16.9	26.6
- Viscosity Index	101	95	96
- Flash Point (COC), °C	240	248	254
- Pour Point, °C	-27	-9	-12
- Foaming Seq.I,(ml/ml)	0/0	0/0	0/0
- Foaming Seq.II,(ml/ml)	0/0	0/0	0/0
- Foaming Seq. III, (ml/ml)	0/0	0/0	0/0

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute: Tel. (662) 537-3000 Ext. 8182, 8278 Fax. (662) 537-3000 Ext. 8199, 8283 or Technical Service Division, Oil Business: Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.