



D-3 HYDRAULIC

Transmission Fluid

Product Description

- *D-3 HYDRAULIC* : Transmission fluid, SAE 10W, uses for a hydraulic powered transmission system of trucks and any machinery

Features/Benefits

- Lubricates and provides wear protection in hydraulic system, such as, hydraulic pump, control valve, hydraulic cylinder of tractors, etc.
- Give excellent prevention of corrosion
- Extends the service life and increases power efficiency of the transmission system

Applications

- Recommended for hydraulic system such as tractors, trucks and bulldozers , forklift, dumping truck and hydraulic system in the industry

Performance Standards

- API CF/SF
- MIL-L-2104D
- CAT TO-2
- ALLISON C-4

Key Properties

	SAE 10W
- Viscosity @ 100 °C, cSt	6.8
- Viscosity Index	115
- Sulfate Ash (%wt.)	1.2
- Flash Point, (COC), °C	224
- Pour Point, °C	-30

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.