



# PTT COMPRESSOR OIL S

## High Quality Compressor Oil

### Description

- PTT COMPRESSOR OIL S 32, 46, 68 : are lubricating oil product for air compressor. They are formulated from high quality paraffinic base oil mixed with high performance additive to extend service life of lubricant and prevent oxidation. PTT compressor oil S also show wear and rust protection.

### Special Properties

- Good oxidation stability and water demulsibility.
- Antiwear and antirust properties
- Long service life, up to 4,000 hr at normal operating condition

### Applications

- Suitable for screw and vane type air compressor which require long life service.
- Can be used in any type of compressor at which OEMs require lubricant formulated with antioxidant, antiwear and rust preventive.

### Reference Standards

### Typical Values

	32	46	68
- Viscosity @ 40 °C, cSt	33.2	47.1	68.9
- Viscosity Index	112	104	103
- Flash Point, °C	224	232	244
- Pour Point, °C	-15	-12	-9
- Total Acid Number, mgKOH/g	0.21	0.22	0.25
- Rust Prevention	Pass	Pass	Pass
- Air Release Property, min	3	5	6
- Foaming Characteristics			
Sequence I, (ml/ml)	Nil / 0	Nil / 0	Nil / 0
Sequence II, (ml/ml)	10 / 0	10 / 0	10 / 0
Sequence III, (ml/ml)	Nil / 0	Nil / 0	Nil / 0

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985 Fax. (662) 239-7858 Lube Hot Line (662) 239-7878