



# PTT COMPRESSOR OIL

## Compressor Oil

### Description

- PTT COMPRESSOR OIL 46, 68, 100, 150: PTT Compressor Oil 46, 68, 100, 150 are high performance petroleum-based compressor oils, produced from high quality base oils with special ashless anti-oxidant, anti-wear additives.

### Special Properties

- Provide high thermal and oxidation stability and good water separability.
- Prolong oil drain intervals and oil separator life

### Applications

- Can be used in air compressors where the manufacturers specify DIN 51506 VDL oils
- Suitable for the lubrication of general types of air compressors where the manufacturers specify oils containing oxidation and rust inhibitors.

### Reference Standards

- DIN 51506 VDL

### Typical Values

	46	68	100	150
- Viscosity @ 40 °C, cSt	46.8	69.2	103.4	153.8
- Viscosity @ 100 °C, cSt	6.85	8.67	11.4	14.9
- Viscosity Index	100	96	96	96
- Flash Point, °C	222	226	232	240
- Pour Point, °C	-9	-6	-6	-6
- Foaming Characteristics				
Sequence I, (ml/ml)	0/0	0/0	0/0	0/0
Sequence II, (ml/ml)	0/0	0/0	0/0	0/0
Sequence III, (ml/ml)	0/0	0/0	0/0	0/0

For more information, contact Fuels & Lubricants Research department, PTT Research and Technology Institute PTT Public Company Limited. Tel: 0-2537-3000 Ext. 2413 and 3248 Fax : 0-2537-3000 Ext. 2236 and 3210 Technical Service Division Tel : 0-2537-2327, 0-2537-2408, 0-2537-2412