



PTT CIRCULAR

Circulating Oil

Descriptions

- PTT CIRCULAR 32, 46, 68, 100, 150 : are multipurpose and circulating oils, produced from high quality paraffinic base oils which provide good oxidation stability. PTT circular 32, 46, 68, 100, 150 are suitable for lubrication systems.

Special Properties

- Good oxidation stability which ensures long service life
- Compatible with rubber seals without reaction and provide good water separation characteristics
- Provide resistance to deposit formation

Applications

- Suitable for circulating lubrication system
- Designed for use in a wide range of industrial operating under low to medium temperature
- Can be used to lubricate bearings, blower, pumps, machine tools and industrial spindles
- Can be used in variety of industrial applications where EP or anti-wear is not required

Reference Standards

Typical Values

	32	46	68	100	150
- Viscosity @ 40 °C, cSt	31.4	47.2	68.98	102.3	151.6
- Viscosity @ 100 °C, cSt	5.3	6.87	8.72	11.3	14.7
- Viscosity Index	100	100	98	96	96
- Flash Point, COC, °C	200	218	222	228	236
- Pour Point, °C	-9	-9	-6	-6	-6
- Copper Corrosion, 3 hr @ 100°C	1b	1b	1b	1b	1b

For more information, contact Fuels & Lubricants Research department, PTT Research and Technology Institute PTT Public Company Limited. Tel: 0-2537-3000 Ext. 2413 and 3248 Fax : 0-2537-3000 Ext. 2236 and 3210 Technical Service Division Tel : 0-2537-2327, 0-2537-2408, 0-2537-2412