



PTT Cylinder Oil

Steam Cylinder Oil

Descriptions

- *PTT Cylinder Oil 50, 90, 250*: are lubricating oil product produced from mineral base oil. PTT Cylinder Oils are used to lubricate many machines in factory as a lubricant in once through feed system

Special Properties

- Low volatility at high temperature
- Non-reactive with machine parts or metals
- Exhibit thermal stability and hydrolytic resistance
- Oxidation resistance

Application

- Suitable for universal machine parts lubrication in industries
- Used in once through feed system especially in rice mill and sawmill
- Lubricate low-to-moderate speed machine

Reference Standards

Typical Values

| | 50 | 90 | 250 |
|---------------------------|----------|-----------|-----------|
| - Color | Dark | Dark | Dark |
| - Viscosity @ 100 °C, cSt | 8.0-15.0 | 18.0-22.0 | 60.0-80.0 |
| - Flash Point, (COC), °C | min 180 | min 200 | min 230 |
| - Pour Point, °C | max 24 | max 30 | max 30 |
| - Sulphur Content, %wt | max 6.2 | max 6.2 | max 6.0 |
| - Aniline Point, °C | max 50 | max 60 | max 70 |

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985 Fax. (662) 239-7858 Lube Hot Line (662) 239-7878