



SEATECH 6000

Diesel Engine Oil for Fishery

Product Descriptions

- **SEATECH 6000** : Premium quality, SAE 15W-40 and 20W-50, multigrade diesel engine oil, specifically developed for diesel engines in fishing vessels, exceeds GLOBAL DHD-1 and API CH-4 standard

Features/Benefits

- Provides best lubrication and prevents wear, corrosion, and rust
- Provides cleanliness with detergent additive added for better cleansing and soot-dispersing
- Provides strong and stable oil film and prevent sludge in oil
- Passes the standard test followed by OEMs
- Enhances fuel economy and prolongs engine life

Applications

- Suitable for fishing vessels that use high speed diesel fuel under normal and severe conditions
- Well suitable for diesel engine which is recommended for a usage of high quality multigrade engine oil including heavy duty turbocharged engine
- Also well suitable for all small fishing vessels' engines

Remark : For PTT Seatech 6000 application, please consult the engine operation manual. In case of old engines with apparent engine oil consumption, SAE 20W-50 viscosity grade is recommended.

Performance Standards

- | | | |
|--------------------------|---|------------------|
| - GLOBAL DHD-1 | - API CH-4, CF-4 | - VOLVO VDS-3 |
| - ACEA E5 / E3 / B4 / B3 | - MAN M 3275 | - MB 228.3 |
| - MTU DDC TYPE 2 | - CUMMINS 20071 / 20072 / 20076 / 20077 | - MACK EO-M PLUS |
| - RENAULT VI RLD | - ALLISON C-4 | |

Key Properties

	SAE 15W-40	SAE 20W-50
- Viscosity @ 100 °C, cSt	15.0	18.8
- Viscosity Index	142	128
- Cold-cranking Simulator, cP	6,510 @ -20 °C	7,960 @ -15 °C
- Flash Point, (COC), °C	242	243
- Pour Point, °C	-27	-27
- Total Base Number, mg KOH/g	12	12

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.