



PTT Radiator Coolant 50:50

Radiator Coolant

Descriptions

- *PTT Radiator Coolant 50:50* : is engine radiator coolant , it is the mixture of mono ethylene glycol (MEG), water and specialty additive. It provides a good cooling, antifreeze and anti-corrosion in the engine coolant system. PTT Radiator Coolant 50:50 meet the requirement of international standard and automotive OEM. It is suitable for used in light duty and heavy duty engine.

Specialty properties

- Cooling the engine coolant system.
- Protect corrosion in the engine coolant system.
- Anti freezing in the engine coolant system.

Application

- Recommend for used in automotive and heavy duty application.

Suggestion :

- Flushing the contamination before using this coolant.
- Used PTT Radiator Coolant 50:50 without additional of water.
- Recommend to change the coolant for heavy duty : 650,000 Km. or 8,000 hrs.
- Recommend to change the coolant for passenger car : 250,000 Km. or 2,000 hrs

Reference standard

- Meet Standard specification: ASTM D3306 , ASTM D6210 , JIS K2234
- Meet OEM requirement:

OEM	Specification	OEM	Specification
Deutz	0199-99-1115/6	Mack	014GS17009
Deutz-MWM	0199-99-2091/8	Waukesha	
Isuzu		Yanmar	
Jenbacher	TA 1000-0201	Ford	WSS-M97B44-D
Kobelco		Mercedeses benz	325.3
MAN B&WAG	D365600	GM	GM6277M
MAN B&WA/S		MAN	324 type SNF
Rover		Volkswagen	TL 774F
DAF	74002		
Jaguar	CMR 8229		
Jaguar	WSS-M97B44-D		
Land Rover	WSS-M97B44-D		

- Specific gravity @ 15.5 °C,	1.060
- Boiling point , °C	108
- pH	8.6
- Freezing point , °C	-40.0
- Reserve alkalinity, mL	3.0
- Nitrate, Nitrite, amine, phosphate, borate content	Nil
- Silicon content	Nil
- Color	green

For more information, contact Fuels & Lubricants Research department, PTT Research and Technology Institute PTT Public Company Limited. Tel: 0-2537-3000 Ext. 2413 and 3248 Fax : 0-2537-3000 Ext. 2236 and 3210 Technical Service Division Tel : 0-2537-2327, 0-2537-2408, 0-2537-2412