

# PTT AROMEX 2000

## Product Description

PTT AROMEX 2000 is lubricating oil product which is used as raw material for producing goods. They are also used as multipurpose lubricating oil in industrial machine.

## Benefits

- High temperature resistance and anti-oxidation
- Long-lasting life and stable for use
- High solvency

## Applications

- Used as raw material in manufacturing that has lubricating oil blended in the products.
- Low to moderate load carrying lubrication
- Drip feed lubrication

*The Moving Innovation* 

# PTT AROMEX 2000

## Typical Characteristics

Tests	Methods	Units	Results
Density at 15 °C	ASTM D 4052-11	g/ml	0.9998
Kinematic Viscosity at 100 °C	ASTM D 445-11	mm <sup>2</sup> /s	9.1
Flash Point (COC)	ASTM D 92-16	°C	234
Pour Point	ASTM D 97	°C	16
Aniline Point	ASTM D 611-12	°C	30.4
Total Sulfur Content	ASTM D 4294	%wt.	4.76
<b>Carbon Type Analysis</b>			
%CA	ASTM D 2140-08	%	47.40
%CN	ASTM D 2140-08	%	29.30
%CP	ASTM D 2140-08	%	23.30

The above mentioned data are only indication and do not present any guarantee. Any deviations of the data are no reason for claim.

## Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttplc.com>

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.