



SEATECH 6500

Diesel Engine Oil for Fishery

Product Descriptions

- **SEATECH 6500** : Premium performance, SAE 15W-40 and 20W-50, multigrade diesel engine oil, specifically developed for superior performance of modern fishing vessels which using high speed diesel fuel.

Features/Benefits

- Excellent engine wear protection and provides best lubrication
- Deliver engine performance and enhances engine cleanliness
- Disperses soot and controls deposit formation on vital engine parts
- Provides strong, stable oil film and prevent sludge in oil
- Prevent rust and corrosion from sea water
- Prolongs engine life and extended oil drain intervals

Applications

- Suitable for fishing vessels that use high speed diesel fuel under normal and severe conditions
- Also well suitable for all small fishing vessels' engines

Remark : For PTT Seatech 6500 application, please consult the engine operation manual. In case of old engines with apparent engine oil consumption, SAE 20W-50 viscosity grade is recommended.

Performance Standards

- API CI-4, CH-4, CG-4, CF-4 / SL
- ACEA E7-12
- MB 228.3
- MTU TYPE 2 (only SAE 15W-40)
- MAN M 3275-1 (only SAE 15W-40)
- VOLVO VDS-3 (only SAE 15W-40)
- MACK EO-N (only SAE 15W-40)
- RENAULT RLD-2 (only SAE 15W-40)
- CUMMINS 20077 / 20076 (only SAE 15W-40)

Key Properties

	<u>15W-40</u>	<u>20W-50</u>		<u>15W-40</u>	<u>20W-50</u>
- Viscosity @ 100 °C, cSt	15.1	19.1	- Density @ 15 °C, g/cm ³	0.876	0.878
- Viscosity @ 40 °C, cSt	115	168	- Flash Point (COC), °C	238	268
- Viscosity Index	137	129	- Pour Point, °C	-36	-33
- Total Base Number, mgKOH/g	10.5	10.5	- Cold-cranking Simulator, cP	6,104 @ -20 °C	7,708 @ -15 °C
- Sulfated Ash, %wt	1.42	1.42			

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited: Tel. (662) 239-7907-08, (662) 239-7910-11
 Fax (662) 239-7858 or Lube Hot Line (662) 239-7878